



## Printed Packing Tape

### Technical Data

<b>Product Description</b>	<p>These tapes are used in electrical insulation purpose, in packaging, sealing and a various other general uses. These tapes are also used for general labelling with printing.</p> <ul style="list-style-type: none"><li>● Bopp film sticky packing tape</li><li>● Water based acrylic</li><li>● Custom colors</li></ul>
<b>Product Construction</b>	<p>Backing: Bopp film Adhesive: Acrylic Adhesive Type: Water Activated Feature: Antistatic Design Printing: Offer Printing</p>
<b>Typical Physical Properties</b>	<p>Adhesion To Peel (N/25mm): <math>\geq 5</math> Holding Power (Hrs): <math>\geq 48</math> Tensile Strength (N/cm): <math>\geq 30</math> Elongation (%): <math>\leq 180</math></p>
<b>Features</b>	<ul style="list-style-type: none"><li>● Excellent adhesion and shear properties</li><li>● Resistance to cold, heat and aging</li><li>● UV stabilized - won't lift off cartons</li><li>● High mechanical strength and good impact resistance</li><li>● Ideal for use in dispensers</li></ul>
<b>Application Ideas</b>	<ul style="list-style-type: none"><li>● Shipping, packaging, bundling, wrapping.</li><li>● Ideal for sealing of cartons, merchandise, pallets</li><li>● Excellent performer for both hand and machine</li></ul>
<b>Storage</b>	<p>Store under normal conditions of 16°C to 27°C and 40 to 60% R.H. in the original carton.</p>
<b>Shelf Life</b>	<p>To obtain best performance, use this product within 24 months from date of manufacture.</p>
<b>Specifications</b>	<p>Any width, length, thickness of tape is 35mic - 90mic, The most common thickness is between 38mic - 53mic. Brand: Buyer's brand is able to printed on paper core.</p>

## Images



**DONGGUAN GUANHONG PACKING INDUSTRY CO.,LTD.**

FURONGSHA IND.DIST., WANGNIUDUN TOWN, DONGGUAN CITY, G.D.CHINA

TEL: 86-769-88518755 FAX: 88518376 E-MAIL: KENNY@DGGUANHONG.COM

<http://www.boppackagingtape.com/>